

Since : 1982

R

Shadaat

s h a d a a b

WIDEST RANGE OF MACHINES INSTALLED WITH PROVEN PERFORMANCE

C-Type Power Press 10Ton to 250Ton

Shadaab Power Presses is the name of Quality





C-Type Power Press

Shadaab brand Power Presses are coming in C Frame, one piece with steel body version from 10Tons to 200Tons capacity in the most economical type of construction with several features. The offered machine is fabricated using premium quality raw material and advanced technology that ensures its durability.

Construction of Frame

Our press machine frame is made of high-grade steel (IS-2062) with high strength, rigidity & stiffness of full loads capacity. The frame bearing the surface is hand-scraped with a fine dimensional axis & frame coated by high-quality paint.

Ram & Liner Box

Ram is made of high-grade steel which bearing surfaces of hard scrapped with aligned by micrometer & dial. Slide are made of high cast-iron material which due to strength & also aligned (0 X 0 Axis) by hand scrapped. Our slide are in two parts for proper alignment.

Shaft

- I. Main Shaft: Main shaft made of alloy steel (EN9) which is tested by IS code. Which is thrown with portable bushes. Bushes that can be fabricated by oil chambers.
- II. Pinion Shaft: Pinion Shaft made of high-grade steel (IS-2062) with (Ghun Metal) bronze bushes. It can be also lubricated by an oil chamber.

Clutch & Rolling Key

Clutch is designed & well supported for mass production under heavy operating conditions. Rolling key made by forging process of special steel.

Brake

It is very sensitive & powerful. It works instantaneously.

Gear

They are of steel casted teeth load capacity gear teeth are generated by precious hobbing machines.

Fly Wheel

It is made of cast iron of high grade & designed to generate required energy & is least liable to put extra load on the motive power.

Lubrication

Oil cups are provided to lubricate all sliding surfaces and moving pants.







Capacity In Tons C-Type

	10Tons	20Tons	30Tons	40Tons	50Tons	75Tons	100Tons	150Tons	200Tons
Stroke adjustable	00-40mm	00-50mm	00-60mm	20-75mm	20-100mm	20-110mm	25-125mm	25-150mm	25-175mm
Distance Bed To Raim	200mm	230mm	255mm	325mm	350mm	425mm	475mm	550mm	650mm
BedSize	300X460mm	350X550mm	400X560mm	460X620mm	500X710mm	550X800mm	610X900mm	700X1000mm	800X1050mm
Crankshaft Dia	80mm	85mm	93mm	120mm	130mm	145mm	160mm	175mm	200mm
Steel Gear Dia	400MM	450mm	500mm	625mm	660-700mm	725-750 mm	775-800mm	1000mm	1200mm
FlyWeel Dia	600mm	650mm	700mm	800mm	850mm	915mm	975mm	1050mm	1250mm
Hole In Raim for Dia Clamping	Ø X L 28X50mm	Ø X L 30X55mm	Ø X L 32X60mm	Ø X L 35X80mm	Ø X L 38X90mm	Ø X L 40X100mm	Ø X L 45X100mm	Ø X L 50X110mm	Ø X L 60X125mm
Bore in Bed	100mm	105mm	115mm	125mm	150mm	160mm	180mm	200mm	225mm
Power Required	1HP	2HP	3HP	4HP	5HP	7.5HP	10HP	12.5HP	15HP
R.P.M Required	1440	1440	1440	1440	1440	1440	1440	1440	1440

Salient Features

	 Salient Features Low tooling cost Reliable Mechanisr 	• Easy to maintain • Quick setting n	 User friendly Stroke length can be adjustable 	 Good versatility Oil Seal Cup lubrication system 	 Competitive Prices Smooth Foot Pedal 				
	Standard Acce	essories							
	• Die Setting Spanner	• Gear Guard Cover	• Oil Cup & Self Lubrication System	• Moter Pulley	 Knock Out System 				
Optional Equipment									
	 Pneumatic Clutch With Photo Safety Curtains 	o To Hand Operated Mechanical Device	• Auto Lubrication System e	 Electrical Moter Starter & V- Belt 	o Strock Countero Extra Base Plate				
		9	Ĩ		AB TECHNO ENGINEERING				

ENGINEERING REP.WORKS. 4/4, Daulat Ganj, Anarbagh, Near Hathipala Water Tank, Indore M.P India - 452007

(Mobile:+91 9300737651/2-3-4, +9198269-34446/7-8-9, +91 9826011656 Email: shadaabpowerpress@gmail.com



Plot No. 183/A & 184/A Sector-F, Industrial Estate Sanwer Road, Indore M.P India- 452015

(Mobile:+91 9300737651/2-3-4, +9198269-34446/7-8-9, +91 9826011656 Email: technopowerpress@gmail.com